



Intelligent NVR AM-i240-UHD 40ch 2HDD Intelligent NVR



Superior Engineering Design & Sensational Image Quality

AM-i240-UHD 40ch 2HDD Intelligent NVR



H.265+ VIDEO
COMPRESSION



ULTRA HD
RESOL UTION



HDMI



VGA



VIDEO
ANALYTICS



SMART RECORD
& PLAYBACK



RJ45 LAN



TRIGGER
ALARM



P2P CLOUD

Features :

- SS+265/H.265/S+264/H.264 video formats
- Connectable to the third-party network cameras
- Support live view, storage, and playback of the connected camera at up to 16MP resolution
- HDMI and VGA independent outputs
- HDMI Video output at up to 4K resolution
- 2 SATA interface, up to 10TB for 1 HDD
- 1×RJ45 self-adaptive 10/100/1000 Mbps network interface
- VCA detection alarm is supported
- Support cloud upgrade


Technical Specifications

Model No	AM-i240-UHD
Access Channel	40
Incoming Bandwidth	400Mbps
Outgoing Bandwidth	400Mbps
Resolution	16MP/12MP/8MP/6MP/5MP/4MP/3MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Preview decoding capability	16MP*2, 12MP*3, 8MP*4, 6MP*4, 5MP*6, 4MP*8, 3MP*9, 1080P*16, 720P*32, 4CIF*40
Playback decoding capability	16MP*2, 12MP*3, 8MP*4, 6MP*4, 5MP*6, 4MP*8, 3MP*9, 1080P*16, 720P*16
Video Output	independent HDMI and VGA outputs
HDMI Output	HDMI:800*600(60Hz), 1024*768(60Hz), 1280*720(50Hz/60Hz), 1280*800(60Hz), 1366*768(60Hz), 1440*900(60Hz), 1920*1080(50Hz/60Hz), 2560*1440(30Hz/60Hz), 2560*1600(60Hz), 3840*2160(30Hz/60Hz)
VGA Output	VGA:800*600(60Hz), 1024*768(60Hz), 1280*720(50Hz/60Hz), 1280*800(60Hz), 1366*768(60Hz), 1440*900(60Hz), 1920*1080(50Hz/60Hz)
Multi-screen Display	1/2/3/4/5/6/7/8/9/10/12/13/16/20A/20B/25/32/36/40
Third-party Camera Access	ONVIF;RTSP
Audio Input	1-ch, 3.5mm
Audio Output	1-ch, RCA (Linear, 1 KΩ)
Liveview display	Independent Output: HDMI: 1/2/3/4/5/6/7/8/9/10/12/13/16/20A/20B/25/32/36/40 VGA: 1/2/3/4/5/6/7/8/9/10/12/13/16/20A/20B/25/32/36/40
Compression	
Video	S+265;H.265;S+264;H.264
Audio	G711A;G711U;AAC;ADPCM_DIV4
Stream Type	Video;Video & Audio
Network	
Network Protocol	ARP;DDNS;DHCP;DNS;Easy DDNS;FTP;HTTP;HTTPS;ICMP;IGMP;IPv4;IPv6;Multicast; NFS;NTP;PPPoE;RTCP;RTP;RTSP;SMB/CIFS;SMTP;SNMP;SRTP;SSH;SSL;TLSv1.2, TLSv1.3;TCP/IP;UDP;Unicast;UPnP
System Compatibility	ONVIF(profile T/S/G)
Web	IE10+;Firefox52+;Edge89+;Safari11+;Chrome57+
Record Playback	
Multi-channel Playback	16
Record Mode	Manual recording;alarm recording;Schedule recording
Backup	USB storage device
Playback Function	Play/Pause/Stop/Slow/Speed/Backwards 30s/Forwards 30s/Full screen/backup(video Editing)/Step/Digital Zoom
Alarm	
General Alarm	Motion;Mask Alarm;Alarm Input(IPC);Video Loss;Alarm Input(NVR);Manual Alarm
Alert Alarm	IP Conflict;MAC Conflict;Network Disconnected;No disk;Illegal Access;Disk group space alert;Disk Full;Disk R/W error; Video Abnormal;Abnormal found in smart of disk;Abnormal temperature of the disk;IPC voltage abnormal;RTC failure
Intelligent Analytics	
VCA Detection by Camera	Tripwire;Double Tripwire;Perimeter;Object Abandon;Object Missing;Loiter;Running;Parking;Heatmap;Lens Dignose;Scene Switch Dignose;Signal Abnormal Detection;Signal Loss Detection;Plate License Recognition;On Duty Detection; Crowd Detection;Parking guard;Safety Helmet Detection;Electric vehicle testing;People Counting;Link To Tracking; Fireworks detection;Environmental temperature measurement;Face Detection;Human body temperature measurement; Advanced Intelligence
VCA Search	Heatmap;Early-warning search;Behavior Search;Plate license search;Search safety helmet;Thermographic retrieval;Duty search;Electric vehicle retrieval;Facial search

Technical Specifications

Model No.	AM-i240-UHD
External Port	
HDD	2 SATA ports, up to 10TB for a single HDD. The maximum HDD capacity varies with environment temperature
USB	1*USB2.0; 1*USB3.0
HDMI	1*HDMI(supports up to 4K resolution output)
VGA	1*VGA
RJ-45	2*RJ-45, 10/100/1000 Mbps self-adaptive Ethernet port
SATA	2 SATA interface
RS232	1*RS232
RS485	1*RS485
Alarm I/O	16channel in; 4channel out
General Parameter	
UI Language	English
Power Supply	DC12V 3.3A
Power Consumption	< 15W(HDD not included, idling)
NetWeight	2.25 kg
GrossWeight	3.85 kg
Boundary Dimensions	440(L)277(W)47.5(H)mm
Package Dimensions	510(L)150(W)385(H)mm
Operating Temperature	-10°C~+55°C
Operating Humidity	10%~90%RH
Storage Temperature	-10°C~+55°C
Storage Humidity	10%~90%RH

DIMENSIONS (Unit: mm)



Physical Interfaces

